

IN THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Currently Amended) A medical electrical lead, comprising:
a lead body including a proximal end;
a sensor capsule coupled to the lead body; and
a sensor bus coupled to the sensor capsule and extending through the lead body to the lead body proximal end, the sensor bus comprising:
an elongate coil conductor forming a lumen of a first diameter,
an elongate cable conductor extending within the lumen of the coil conductor, and
an electrically insulative layer formed as a coating on an exterior surface of the cable conductor, wherein an outer diameter of the insulative layer is of a second diameter less than the first diameter of the lumen of the coil conductor such that an average gap exists between the insulative layer and an interior surface of the lumen of the coil conductor, wherein the insulative layer has positioned between the cable conductor and the coil conductor, having a relative dielectric coefficient less than approximately 10, and wherein the insulative layer has an inner diameter ~~the insulative layer having an outer diameter and an inner diameter, the outer diameter being greater than approximately 1.4 times the inner diameter; and~~
~~an average gap between the outer diameter of the insulative layer and the coil conductor.~~
2. (Cancelled)

3. (Original) The lead of claim 1, wherein the relative dielectric coefficient of the insulative layer is less than approximately 3.
4. (Original) The lead of claim 2, wherein the outer diameter of the insulative layer is greater than approximately 2 times the inner diameter of the insulative layer.
5. (Currently amended) The lead of claim 1, wherein the average gap is less than approximately 0.003 inch.
6. (Original) The lead of claim 5, wherein the average gap is less than approximately 0.001 inch.
7. (Cancelled)
8. (Original) The lead of claim 1, wherein the insulative layer comprises a fluoropolymer.
9. (Original) The lead of claim 8, wherein the fluoropolymer is ETFE.
10. (Original) The lead of claim 1, wherein the insulative layer comprises a silicone.
11. (Original) The lead of claim 1, wherein the insulative layer comprises a polyimide.
12. (Original) The lead of claim 1, wherein the insulative layer comprises polyurethane.

13. (Original) The lead of claim 1, wherein the coil conductor includes an MP35N alloy wire having a core of a lower resistance than the MP35N alloy.
14. (Original) The lead of claim 1, wherein the cable conductor includes an MP35N alloy wire having a core of a lower resistance than the MP35N alloy.
15. (Original) The lead of claim 1, wherein the cable conductor includes an outer diameter less than approximately 0.008 inch.
16. (Original) The lead of claim 1, wherein the coil conductor includes an inner diameter less than approximately 0.020 inch.
17. (Original) The lead of claim 1, wherein the coil conductor includes a longitudinal axis and a distal portion extending laterally away from the longitudinal axis to couple with the sensor capsule.
18. (Original) The lead of claim 1, wherein the sensor capsule includes a feedthrough pin and the cable conductor is coupled to the feedthrough pin.
19. (Original) The lead of claim 1, wherein the lead body includes a plurality of lumens and the sensor bus extends through a one of the plurality of lumens.
20. (Currently Amended) An implantable medical electrical lead, comprising:
 - a lead body including a proximal end;
 - a sensor capsule coupled to the lead body; and
 - a sensor bus coupled to the sensor capsule and extending through the lead body to the lead body proximal end, the sensor bus comprising:
 - an elongate coil conductor forming a lumen of a first diameter,

an elongate cable conductor extending within lumen of the the coil conductor and electrically isolated from the coil conductor,

an electrically insulative layer formed as a coating on an exterior surface of the cable conductor, wherein an outer diameter of the insulative layer is of a second diameter less than the first diameter of the lumen of the coil conductor such that an average gap exists between the insulative layer and an interior surface of the lumen of the coil conductor, wherein the insulative layer has a relative dielectric coefficient less than approximately 10, and wherein the insulative layer has an inner diameter,

~~an average gap between the cable conductor and the coil conductor, and~~

~~means to reduce a~~ wherein the insulative layer reduces capacitance between the cable conductor and the coil conductor over an implanted life of the lead, the ~~means~~ layer comprising a polymer material having a ~~dielectric coefficient less than approximately 10 and~~ filling greater than approximately 50% of the average gap between the the insulative layer of the cable conductor and the interior surface of the lumen of the coil conductor.

21. (Original) The lead of claim 20, wherein the polymer material fills greater than 80% of the average gap between the cable conductor and the coil conductor.

22. (Original) The lead of claim 20, wherein the relative dielectric coefficient of the polymer material is less than approximately 3.

23. (Original) The lead of claim 20, wherein the polymer comprises a fluoropolymer.

24. (Original) The lead of claim 23, wherein the fluoropolymer is ETFE.
25. (Original) The lead of claim 20, wherein the insulative layer comprises a silicone.
26. (Original) The lead of claim 20, wherein the insulative layer comprises a polyimide.
27. (Original) The lead of claim 20, wherein the insulative layer comprises a urethane.
28. (Original) The lead of claim 20, wherein the coil conductor includes an MP35N alloy wire having a core of a lower resistance than the MP35N alloy.
29. (Original) The lead of claim 20, wherein the cable conductor includes an MP35N alloy wire having a core of a lower resistance than the MP35N alloy.
30. (Original) The lead of claim 20, wherein the cable conductor includes an outer diameter less than approximately 0.008 inch.
31. (Original) The lead of claim 20, wherein the coil conductor includes an inner diameter less than approximately 0.020 inch.
32. (Original) The lead of claim 20, wherein the coil conductor includes a longitudinal axis and a distal portion extending laterally away from the longitudinal axis to couple with the sensor capsule.
33. (Original) The lead of claim 20, wherein the sensor capsule includes a feedthrough pin and the cable conductor is coupled to the feedthrough pin.

P0020093

Applicants: Mark T. Marshall et al.

Response to Office Action of March 26, 2007

Serial No. 10/759,997

Page 7

34. (Original) The lead of claim 20, wherein the lead body includes a plurality of lumens and the sensor bus extends through a one of the plurality of lumens.